



DETAIL A



DETAIL A

NOTE :

1. CONTROLLING DIMENSION : INCH
2. LEAD FRAME MATERIAL : COPPER 194
3. DIMENSION "D" DOES NOT INCLUDE MOLD FLASH, TIE BAR BURRS AND GATE BURRS. MOLD FLASH, TIE BAR BURRS AND GATE BURRS SHALL NOT EXCEED 0.006"[0.15mm] PER END DIMENSION "E1" DOES NOT INCLUDE INTERLEAD FLASH. INTERLEAD FLASH SHALL NOT EXCEED 0.010"[0.25mm] PER SIDE.
4. DIMENSION "b" DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.003"[0.08mm] TOTAL IN EXCESS OF THE "b" DIMENSION AT MAXIMUM MATERIAL CONDITION. DAMBAR CANNOT BE LOCATED ON THE LOWER RADIUS OR THE FOOT. MINIMUM SPACE BETWEEN PROTRUSION AND AN ADJACENT LEAD TO BE 0.0028"[0.07mm]
5. TOLERANCE : ±0.010"[0.25mm] UNLESS OTHERWISE SPECIFIED.
6. OTHERWISE DIMENSION FOLLOW ACCEPTABLE SPEC.
7. REFERENCE DOCUMENT : JEDEC SPEC MO-137

SYMBOLS	DIMENSIONS IN MILLIMETERS			DIMENSIONS IN INCHES		
	MIN	NOM	MAX	MIN	NOM	MAX
A	1.35	1.60	1.75	0.053	0.063	0.069
A1	0.10	0.15	0.25	0.004	0.006	0.010
A2	—	—	1.50	—	—	0.059
b	0.20	—	0.30	0.008	—	0.012
C	0.18	—	0.25	0.007	—	0.010
D	4.80	4.85	5.00	0.189	0.191	0.197
ZD	—	0.20	—	—	0.008	—
E	5.79	5.99	6.20	0.228	0.236	0.244
E1	3.81	3.91	3.99	0.150	0.154	0.157
L	0.41	0.71	1.27	0.016	0.028	0.050
e	—	0.64	—	—	0.025	—
y	—	—	0.076	—	—	0.003
θ	0°	—	8°	0°	—	8°

CUSTOMER :

ZYWYN CORPORATION

APPROVED BY

DATE

TITLE:

DRAW BY:

CHECK BY:

APPROVAL:

APPROVAL:

08/31/00

09/10/00

09/10/00

09/10/00

16L NARROW BODY FINE PITCH
STANDARD SMALL OUTLINE
PACKAGE DRAWING

DWG. NO. PO-SSOP-005

UNIT :

INCH

SCALE : 12/1

REV. 1

SHEET 1 OF 1